Creating the maple initialization file maple.ini

```
> currentdir("C:\\Program Files\\Maple 2015");
```
$$\text{"C:\textbackslash Program Files\textbackslash Maple 2015"} \tag{1}$$

```
> currentdir();
```
$$\text{"C:\textbackslash Program Files\textbackslash Maple 2015"} \tag{2}$$

```
> currentdir(Users);
```
$$\text{"C:\textbackslash Program Files\textbackslash Maple 2015"} \tag{3}$$

```
> currentdir();
```
$$\text{"C:\textbackslash Program Files\textbackslash Maple 2015\textbackslash Users"} \tag{4}$$

```
> str:="Homelib:=\"C:\\\\cygwin64/home/fgarvan/maple/mylib\":";
```
$$str := \text{"Homelib:="C:\textbackslash\textbackslash cygwin64/home/fgarvan/maple/mylib":"} \tag{5}$$

```
> str2:="libname := libname, Homelib:";
```
$$str2 := \text{"libname := libname, Homelib:"} \tag{6}$$

```
> fd := fopen("maple.ini",WRITE);
```
$$fd := 0 \tag{7}$$

```
> fprintf("maple.ini", %s\n,str);
```
$$49 \tag{8}$$

```
> fprintf("maple.ini","\n");
```
$$1 \tag{9}$$

```
> fprintf("maple.ini", %s\n,str2);
```
$$28 \tag{10}$$

```
> fclose(fd);
```